

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF CLAIMS:

1-19. (cancelled).

20. (previously presented) An information recording apparatus which irradiates a laser light onto a recording medium and forms a recording mark corresponding to a recording signal, comprising:

a light source which emits the laser light; and

a signal generating unit which generates a recording pulse signal driving the light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark,

wherein the signal generating unit makes a level of the recording pulse signal corresponds to a recording power ensuring reproduction compatibility in a mark period corresponding to a long mark and corresponds to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

21. (previously presented) An information recording apparatus which irradiates a laser light onto a recording medium

and forms a recording mark corresponding to a recording signal, comprising:

a light source which emits the laser light; and

a signal generating unit which generates a recording pulse signal driving the light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark,

wherein the signal generating unit makes a level of the recording pulse signal corresponds to a recording power having waveform distortion equal to or smaller than a predetermined value in a mark period corresponding to a long mark and corresponds to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

22. (previously presented) An information recording apparatus which irradiates a laser light onto a recording medium and forms a recording mark corresponding to a recording signal, comprising;

a light source which emits the laser light; and

a signal generating unit which generates a recording pulse signal driving the light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark,

wherein the signal generating unit makes a level of the recording pulse signal corresponds to a recording power ensuring reproduction compatibility and having waveform distortion equal to or smaller than a predetermined value in a mark period corresponding to a long mark and corresponds to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

23. (previously presented) The information recording apparatus according to claim 20, wherein the recording power ensuring the reproduction compatibility is a recording power having a modulation degree within a predetermined range.

24. (previously presented) The information recording apparatus according to claim 23, wherein the recording power having the modulation degree within the predetermined range is a recording power having a modulation degree equal to or larger than 60%.

25. (previously presented) The information recording apparatus according to claim 21, wherein the recording power having the waveform distortion equal to or smaller than the predetermined value is a recording power having waveform distortion equal to or smaller than 10%.

26. (previously presented) The information recording apparatus according to claim 21, wherein the recording power having the waveform distortion equal to or smaller than the predetermined value is a recording power having waveform distortion of 0.

27. (previously presented) The information recording apparatus according to claim 20, wherein the recording power having the asymmetry within the predetermined range is a recording power having asymmetry within a range of -0.05 to 0.15.

28. (previously presented) The information recording apparatus according to claim 20, wherein the short mark is a shortest mark, and the long mark is a mark other than the short mark.

29. (previously presented) The information recording apparatus according to claim 20, wherein the short mark is a shortest mark and a second shortest mark, and the long mark is a mark other than the short mark.

30. (previously presented) The information recording apparatus according to claim 20, wherein the short mark is a mark having a level of no largest magnitude, and the long mark is a mark having a level of the largest magnitude.

31. (previously presented) The information recording apparatus according to claim 20, wherein the recording pulse signal has a same level for all the long marks.

32. (previously presented) The information recording apparatus according to claim 20, wherein the recording pulse signal has different levels for each of the short marks.

33. (previously presented) An information recording method which irradiates a laser light onto a recording medium and forms a recording mark corresponding to a recording signal, comprising:

a signal generating process which generates a recording pulse signal driving a light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark; and

an irradiating process which irradiates a laser pulse onto the recording medium based on the recording pulse signal,

wherein the signal generating process makes a level of the recording pulse signal corresponds to a recording power ensuring reproduction compatibility in a mark period corresponding to a long mark and correspond to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

34. (previously presented) An information recording method which irradiates a laser light onto a recording medium and forms a recording mark corresponding to a recording signal, comprising

a signal generating process which generates a recording pulse signal driving a light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark; and

an irradiating process which irradiates a laser pulse onto the recording medium based on the recording pulse signal,

wherein the signal generating process makes a level of the recording pulse signal corresponds to a recording power having waveform distortion equal to or smaller than a predetermined value in a mark period corresponding to a long mark and correspond to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

35. (previously presented) An information recording method which irradiates a laser light onto a recording medium and forms a recording mark corresponding to a recording signal, comprising:

a signal generating process which generates a recording pulse signal driving a light source based on the recording signal

and including a mark period for forming the recording mark and a space period for forming no recording mark; and

an irradiating process which irradiates a laser pulse onto the recording medium based on the recording pulse signal,

wherein the signal generating process makes a level of the recording pulse signal corresponds to a recording power ensuring reproduction compatibility and having waveform distortion equal to or smaller than a predetermined value in a mark period corresponding to a long mark and correspond to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

36. (currently amended) A ~~computer program product in a~~ computer-readable recording medium with a computer program recorded thereon executed in an information recording apparatus including a light source, irradiating a laser light onto a recording medium to form a recording mark corresponding to a recording signal, and making the information recording apparatus execute:

a signal generating process which generates a recording pulse signal driving the light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark; and

an irradiating process which irradiates a laser pulse onto the recording medium based on the recording pulse signal,

wherein the signal generating process makes a level of the recording pulse signal corresponds to a recording power ensuring reproduction compatibility in a mark period corresponding to a long mark and correspond to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

37. (currently amended) A ~~computer program product in a~~ computer-readable recording medium with a computer program recorded thereon executed in an information recording apparatus including a light source, irradiating a laser light onto a recording medium to form a recording mark corresponding to a recording signal, and making the information recording apparatus execute:

a signal generating process which generates a recording pulse signal driving the light source based on the recording signal and including a mark period for forming the recording mark and a space period for forming no recording mark; and

an irradiating process which irradiates a laser pulse onto the recording medium based on the recording pulse signal,

wherein the signal generating process makes a level of the recording pulse signal corresponds to a recording power



having waveform distortion equal to or smaller than a predetermined value in a mark period corresponding to a long mark and correspond to a recording power having asymmetry within a predetermined range in a mark period corresponding to a short mark, thereby to generate the recording pulse signal.

38. (currently amended) A ~~computer program product in a~~ computer-readable recording medium with a computer program recorded thereon executed in an information recording apparatus including a light source, irradiating a laser light onto a recording medium to form a recording mark corresponding to a recording signal, and making the information recording apparatus execute:

a signal generating process which generates a recording pulse signal driving the light source based on the recoding signal and including a mark period for forming the recording mark and a space period for forming no recording mark; and

an irradiating process which irradiates a laser pulse onto the recording medium based on the recording pulse signal,

wherein the signal generating process makes a level of the recording pulse signal corresponds to a recording power ensuring reproduction compatibility and having waveform distortion equal to or smaller than a predetermined value in a mark period corresponding to a long mark and correspond to a recording power having asymmetry within a predetermined range in

a mark period corresponding to a short mark, thereby to generate the recording pulse signal.